

TR(灰色)

TR シリーズ							
呼称	外径 (mm)	内径 (mm)	自由長 (mm)	定数 (kgf/mm)	たわみ (mm)	荷重 kgf {N}	密着長 (mm)
TR14.5 X 20	14.5	9	20	1.10	10.0	11 {107.9}	8
25			25	0.88	12.5		10
30			30	0.73	15.0		12
35			35	0.63	17.5		14
40			40	0.55	20.0		16
45			45	0.49	22.5		18
50			50	0.44	25.0		20
55			55	0.40	27.5		22
60			60	0.37	30.0		24
65			65	0.34	32.5		26
70			70	0.31	35.0		28
75			75	0.29	37.5		30
80			80	0.28	40.0		32
90			90	0.24	45.0		36
100			100	0.22	50.0		40
125	125	0.18	62.5	50			
TR 17 X 25	17	11	25	1.52	12.5	19 {186.3}	10
30			30	1.27	15.0		12
35			35	1.09	17.5		14
40			40	0.95	20.0		16
45			45	0.84	22.5		18
50			50	0.76	25.0		20
55			55	0.69	27.5		22
60			60	0.63	30.0		24
65			65	0.58	32.5		26
70			70	0.54	35.0		28
75			75	0.51	37.5		30
80			80	0.48	40.0		32
90			90	0.42	45.0		36
100			100	0.38	50.0		40
125			125	0.30	62.5		50
150	150	0.25	75.0	60			
TR 21 X 30	21	13	30	1.40	15.0	21 {206}	12
35			35	1.20	17.5		14
40			40	1.05	20.0		16
45			45	0.93	22.5		18
50			50	0.84	25.0		20
55			55	0.76	27.5		22
60			60	0.70	30.0		24
65			65	0.65	32.5		26
70			70	0.60	35.0		28
75			75	0.56	37.5		30
80			80	0.53	40.0		32
90			90	0.47	45.0		36
100			100	0.42	50.0		40
125			125	0.34	62.5		50
150			150	0.28	75.0		60
TR 26 X 30	26	16.5	30	2.73	15.0	41 {402}	12
35			35	2.34	17.5		14
40			40	2.05	20.0		16
45			45	1.82	22.5		18
50			50	1.64	25.0		20

TR(灰色)

TR シリーズ							
呼称	外径 (mm)	内径 (mm)	自由長 (mm)	定数 (kgf/mm)	たわみ (mm)	荷重 kgf {N}	密着長 (mm)
TR 26 X 55	26	16.5	55	1.49	27.5	41 {402}	22
60			60	1.37	30.0		24
65			65	1.26	32.5		26
70			70	1.17	35.0		28
75			75	1.09	37.5		30
80			80	1.03	40.0		32
90			90	0.91	45.0		36
100			100	0.82	50.0		40
110			110	0.75	55.0		44
125			125	0.66	62.5		50
150			150	0.55	75.0		60
175			175	0.47	87.5		70
200			200	0.41	100.0		80
TR 32 X 40			32	21	40		2.55
45	45	2.27			22.5	18	
50	50	2.04			25.0	20	
60	60	1.70			30.0	24	
70	70	1.46			35.0	28	
80	80	1.28			40.0	32	
90	90	1.13			45.0	36	
100	100	1.02			50.0	40	
110	110	0.93			55.0	44	
125	125	0.82			62.5	50	
150	150	0.68			75.0	60	
175	175	0.58			87.5	70	
200	200	0.51			100.0	80	
250	250	0.41			125.0	100	
300	300	0.34	150.0	120			
TR 39 X 40	39	26	40	2.75	20.0	55 {539}	16
45			45	2.44	22.5		18
50			50	2.20	25.0		20
60			60	1.83	30.0		24
70			70	1.57	35.0		28
80			80	1.38	40.0		32
90			90	1.22	45.0		36
100			100	1.10	50.0		40
110			110	1.00	55.0		44
125			125	0.88	62.5		50
150			150	0.73	75.0		60
175			175	0.63	87.5		70
200			200	0.55	100.0		80
250			250	0.44	125.0		100
300	300	0.37	150.0	120			
TR 46 X 50	46	32	50	2.48	25.0	62 {608}	20
60			60	2.07	30.0		24
70			70	1.77	35.0		28
80			80	1.55	40.0		32
90			90	1.38	45.0		36
100			100	1.24	50.0		40
110			110	1.13	55.0		44
125			125	0.99	62.5		50
150	150	0.83	75.0	60			

TR(灰色)

TR シリーズ							
呼称	外径 (mm)	内径 (mm)	自由長 (mm)	定数 (kgf/mm)	たわみ (mm)	荷重 kgf {N}	密着長 (mm)
TR 46 X 175	46	32	175	0.71	87.5	62 {608}	70
200			200	0.62	100.0		80
250			250	0.50	125.0		100
300			300	0.41	150.0		120